

# Modeling of Soil Loss and Identification of Erosion Hot Spot Areas Using RUSLE Integrated with GIS for Appropriate Conservation Practices in Muga Watershed, Highlands of Ethiopia

Girum Getachew Demeke<sup>1\*</sup> Tesfa Gebrie Andualem<sup>2</sup>

1.Department of Natural Resources Management, Debre Tabor University, Debre Tabor, Ethiopia

2.Department of Hydraulic and Water Resources Engineering, Debre Tabor University, Debre Tabor, Ethiopia

## Abstract

Over cultivation, deforestation and free grazing are major factors facilitating soil erosion. Nowadays; in lower parts of Muga watershed soil erosion become as a continuous environmental problem. In this study an attempt has been made to modeling soil loss and identify the most erosion sensitive areas by using Revised Universal Soil Loss Equation integrated with GIS and remote sensing techniques for planning appropriate conservation measures in Muga watershed. The annual soil loss amount was estimated by using the Revised Universal Soil Loss Equation (RUSLE). Digital Elevation Model, digital soil map, thirty years rainfall records of six stations, and land cover data (Landsat images) were used to develop RUSLE soil loss variables. The annual soil loss rate from the catchment were estimated by integrating RUSLE parameters using raster calculator tool. The annual soil loss rate varies between 0.02 ton/ha/yr and 41.789 ton/ha/yr. The total annual soil loss in the watershed was 59751.41 tones, of these, 12806.15 tons were lost from 371.19 km<sup>2</sup>, 26562.44 tons from 214.30 km<sup>2</sup>, 15300.94 tons from 50.52 km<sup>2</sup>, 4059.05 tons from 4.61 km<sup>2</sup>, and 1022.83 tons from 0.37 km<sup>2</sup> of land per year. The rate of soil erosion was high in the lower part of the watershed. Slope gradient and length factor was the main factor for soil erosion increment followed by Support Practice (P) factor. As result of soil erosion cross tabulation; steep slopes, Rendzic leptosols and dominantly cultivated areas were detected as very severe erosivity. Therefore, the lower parts of the study needs to undertake effective soil and water conservation practices.

**Keywords:** Soil loss, RUSLE, GIS, Remote sensing, Moga Watershed, Erosion hot spot areas

**DOI:** 10.7176/JEES/9-10-03

**Publication date:** October 31<sup>st</sup> 2019

## 1. Introduction

Soil erosion by runoff is the process of detaching and transporting of soil particles by flowing water to downstream areas (Kunta, 2009). Soil erosion has an adverse effect for developing countries like Ethiopia, since agriculture is the main source of income and food, which is dependent on the soil fertility (Hurni, 1993). Soil erosion has been considered as the most serious land problem, due to its on-site and off-site effects on the food security and the economy of the country (Hurni, 1993; Sutcliffe, 1993; Lulseged and Vlek, 2005).

Soil erosion is mostly caused by accelerated soil erosion which is principally favored by human activities. Soil erosion has a profound impacts on crop production, reservoir sedimentation, and downstream flooding (Hurni et al., (2015), Haregeweyn et al., (2015b)); while as economic costs and ecosystem services has been well documented by Hurni et al., (2015) and Haregeweyn et al., (2015a,b, 2016) respectively. As compared to flat areas, soil erosion at the steep areas has high adverse effects (Taye et al., (2013) and Descheemaeker et al., (2006). But for overall rates of total soil loss, at regional or national scales, very few estimates are available according to Sonneveld et al., (2011). Due to soil erosion, in Ethiopian highlands 23400 million metric tons soil is lost per year (FAO, 1984; Hurni, 1993).

In developing countries like Ethiopia unsuitable land cultivation, overgrazing and deforestation have accelerated soil erosion rates per hectare of land (Reusing et al., 2000; Tamene and Vlek, 2008; Zemenu and Amare, 2014). The expansion of agricultural practices had been increasing the amount of soil erosion in the Ethiopian high lands (Aster, 2004; Zemenu and Amare, 2014). In Muga watershed between 1986 and 2009; the cultivated land had been increased from 40.01% to 76.47% (Demeke and Andualem, 2018).

Amount of soil loss is affected by different factors like overgrazing and cultivation, population pressure, deforestation, erosive rainfall and rugged terrain features (EHRS, 1984). Identifying highly soil erodible areas is important to mitigate the influences of soil degradation and to assist the conservation and rehabilitation practices for basins. In this regard, integrating the USLE model and GIS technique for estimating annual soil loss contributes a lot to alleviate the existing problem by identifying soil degradation areas.

Therefore, this study is conducted to address the following objectives: (1) to estimate the amount of soil loss rate, (2) to generate erosion severity and erosion hazard maps and (3) to identify erosion hotspot areas for appropriate conservation measures.

## 2. Methodology

### 2.1 Description of the Study Area

Muga watershed is found in Amhara region between 10°6'30''N to 10°43'30''N latitude and 37°49'00''E to 38°16'30''E longitude and it has an area of 641 km<sup>2</sup> (Figure 1). Muga River originates from Choke Mountain at an elevation of 4092 m.a.s.l and flows to Abbay River. The agro-climatic zones of the study area are attributed by wet/moist dega (temperate like climate-highlands) and kola (hot and arid type) zones (NMSA, 2001). The study area characterized as a wet season from June to September and dry season from October to May. The mean annual precipitation of the study area is found 1445 mm, and the minimum and maximum temperature are 5 °C and 25 °C respectively. Soil groups which are found in the study area are Eutric Vertisols (56.68%), Chromic Luvisols (28.55%), Humic Nitosols (5.42%) and Rendizic Leptosols (9.35%). The topography of study area ranges between 1199 m.a.s.l and 4092 m.a.s.l (Demeke and Andualem, 2018).




Figure 1. Location of study area

### 2.2 Sources and Techniques of Data Collection

For this study, both secondary and primary data sources were used. By using Global Positioning System (GPS) instrument, both field survey and observation was conducted for actual primary data collection. The land use land cover map of the study area were developed by using supervised image classification and Ground Control Points (GCPs) for validating the accuracy of image classification. Secondary data were collected from different organizations like meteorological data (1986-2015) from National Meteorology Agency (NMA); soil and Digital Elevation Model (20\*20 m) from Ministry of Water, Irrigation and Electricity (MoWIE), land use/cover map of 2013 from Ethiopian mapping agency. The slope length–steepness (LS) factor was derived from digital elevation model.

### 2.3 Soil Loss Estimation

In this study, Revised Universal Soil Loss Equation (RUSLE) integrated with Remote sensing and GIS technique was used to estimate the mean annual soil loss. RUSLE is expressed as equation 1:

$$A \text{ (tons/ha/year)} = R * K * LS * C * P \text{----- (1)}$$

Where A is the annual soil loss (tons/ha/year); R is the rainfall erosivity factor (MJ mm/ha/h/yr); K is the soil erodibility factor [tons/ha/year]; LS is the slope length-steepness factor (dimensionless); C is the cover and management factor (dimensionless, between 0 and 1); and P is the support practice factor (dimensionless, ranges from zero to one).

To calculate the amount of soil loss rate in the study area, all the erosion factors (R, K, LS, C, and P) were determined based on the previous recommendations to Ethiopian highlands (Hurni, 1985a). The spatial distribution of soil loss was developed by integrating the erosion influencing factors in Arc GIS the raster calculator geo-processing tool.



Table 4 Major land uses with their corresponding C-value

No.	Major land use/cover	Source	C-value
1	Afro-alpine	BCEOM, 1998	0.01
2	Dominantly cultivated	Hurni,1985	0.15
3	Moderately cultivated	Hurni,1985	0.1
4	Urban	BCEOM, 1998	0.05

The RUSLE model was simulated by GIS and remote sensing techniques to identify erosion hot spot areas (Figure 2).




Figure 2. Conceptual Framework of Soil Loss Analysis by RUSLE Model

### 3. Result and Discussion

#### 3.1 Estimation of Soil Loss and identification of hotspot areas

In this study, RUSLE equation was integrated with Arc GIS 10.1 technique to conduct cell by cell calculation of mean annual soil loss rate (ton/ha/year) and to identify high erosion hot spot areas in Muga Watershed. Raster map of each RUSLE parameters was derived from different data sources and discussed as follows.

##### Rain Fall Erosivity(R) Factor

The values of R-factor (Table 5) in Muga watershed ranges from 664.53 (Mota station) to 772.74 (Bichena station). The R- factor values for each station was assigned with color (Figure 3a).

Table 5 R-factor values of rainfall stations

No.	Station Name	Elevation (mm)	Mean annual rainfall (mm)	R-Factor
1	Debre Markos	2446	1360.69	756.59
2	Mota	2417	1196.88	664.53
3	Yetmen	2418	1322.97	735.39
4	Yetnora	2420	1215.51	675
5	Bichena	2532	1389.43	772.74

##### Soil Erodibility (K) Factor

The K-value for each major soil class (Figure 3b) was assigned with special reference to their color (Hurni, 1985). Chromic Luvisols have high k-value (0.158) which are highly affected by erosion. Humic Nitisols and Rendzic Leptosols have low soil erodibility factor with k-value of 0.128 and 0.127 respectively. These soils are less susceptible to detachment and erosion. An area of 182.99 km<sup>2</sup> was highly erodible while 59.92 km<sup>2</sup> was less erodible to soil erosion (Table 6).

Table 6 K-values and area coverage of major soils

No.	Major Soil type	K-value	Area (km <sup>2</sup> )	Area (%)
1	Chromic Luvisols	0.158	182.99	28.55
2	Eutric Vertisols	0.132	363.23	56.68
3	Humic Nitisols	0.128	34.73	5.42
4	Rendzic Leptosols	0.127	59.92	9.35




Figure 3. (a) R-factor and (b) K-factor

**Slope Length and Steepness (LS) factor**

LS-factor was computed using equation (3) suggested by Moore and Bruch (1985); Mitasova and Mitas (1999); and Simms *et al.*, (2003). According to the analysis, the LS factors of the watershed were found in the range of 0.275 to 21.786. Upstream and downstream parts of the watershed had the highest value of LS and middle part of the watershed had the lowest value of LS which was distributed in gently flat to undulating terrain. This indicated that the upstream and downstream parts of the study area are highly sensitive to soil erosion (Figure 4a).

Table 7 Slope length factor (LS) values

No.	LS-value	Area (km <sup>2</sup> )	Area (%)
1	0.275-1.118	367.87	57.91
2	1.119-2.214	212.38	33.43
3	2.215-3.733	50.07	7.88
4	3.734-6.264	4.57	0.72
5	6.265-21.786	0.37	0.06

**Support Practice (P) Factor**

The values of P-factor were found between 0.8 and 1.0 (Table 8). The highest P-value was found in the upstream part of the study area, while the smallest values were observed in the downstream and middle parts of the watershed (Figure 4b).

Table 8 P-Factor values of Muga Watershed

No.	Land use/cover	P-value	Area (km <sup>2</sup> )	Area (%)
1	Afro-alpine	0.8	150.04	23.39
2	Dominantly cultivated	0.95	222.01	34.61
3	Moderately cultivated	0.95	268.53	41.87
4	Urban	1.0	0.81	0.13

**Cover and Management (C) Factor**

As shown in table 9, the value of C-factor was found between 0.01 and 0.15. The dominantly cultivated land has a large value of c-factor (0.15) which is highly vulnerable to erosion. Next to dominantly cultivated land, moderately cultivated land (0.1) is moderately vulnerable to soil erosion. Afro-alpine and urban having the c-factor values of 0.01 and 0.05 respectively are less vulnerable to erosion (Figure 4c).

Table 9: Cover and management (C) values

No.	Land use/cover	C-value	Area (km <sup>2</sup> )	Area (%)
1	Afro-alpine	0.01	150.04	23.39
2	Dominantly cultivated	0.05	222.01	34.61
3	Moderately cultivated	0.1	268.53	41.87
4	Urban	0.05	0.81	0.13




Figure 4. a) LS-factor, b) P-factor c) C-factor

### 3.2 Estimation of Soil Loss

RUSLE is an empirically based model that has the ability to predict long term average annual rate of soil erosion on slopes using data on rainfall pattern, soil type, and topography, conservation, and management practices. Potential annual soil loss was estimated from the product of factors (R, K, LS, C, and P) for the Muga watershed ranges from 0.02 – 41.489 ton/ha/yr. The estimated level of soil loss rate was classified into five classes as shown in figure 5. The classified soil loss map showed that 99.22% of the total area falls under the tolerable rate followed by 0.78% of the total area comes under critical soil.

Table 10 showed that there are 12806.15 tons of soil loss from 371.19 km<sup>2</sup> area, 26562.44 tons soil loss from 214.30 km<sup>2</sup> area, 15300.94 tons soil loss from 50.52 km<sup>2</sup> area, 4059.05 tons soil loss from 4.61 km<sup>2</sup> area, 1022.83 tons soil loss from 0.37 km<sup>2</sup> per year. Results revealed that severe to extreme severe erosion risk areas found in the downstream parts of the watershed due to the presence of steep lands, over cultivation, high rainfall and overgrazing. In the middle part of the watershed, it was observed the low erosion damage area.

Table 10 Erosion intensity class and distribution in the study area

No.	Soil loss rate (ton/ha/yr.)	Severity class	Area (km <sup>2</sup> )	Area (%)	Annual soil loss (ton)	Soil loss (%)
1	0.02-0.67	Very low	371.19	57.91	12806.15	21.43
2	0.671-1.808	Low	214.30	33.43	26562.44	44.45
3	1.809-4.248	Moderate	50.52	7.88	15300.94	25.61
4	4.249-13.355	High	4.61	0.72	4059.05	6.79
5	13.356-41.489	Very high	0.37	0.06	1022.83	1.71
Total			641.00	100.00	59751.41	100.00

Figure 5 showed the spatial distribution of erosion hotspot area and it revealed that the potential soil loss was greater along the steep slope areas. In downstream parts of the watershed over cultivation has been practiced without implementing any soil and water conservation measures which leads to the major soil erosion risks.

Generally, removal of vegetation cover through deforestation, cultivation of steep slope, overgrazing, ploughing the land several times, the practice of removing plant residues, poor physical soil and water conservation measures can cause for high soil loss in the study areas (Demeke and Andualem, 2018).




Figure 5. Soil loss rate distribution map of Muga watershed

### 3.3 Soil Erosion Cross Tabulation Results

Table 11 Relationship between soil erosivity and slope

Erosivity area (km <sup>2</sup> )	Slope (degree)				
	0 – 6.91	6.92 – 13.54	13.55 – 22.19	22.2 – 34.29	34.3 – 73.5
Very low	139.93	129.85	65.90	26.11	5.51
Low	80.75	57.23	33.60	27.25	13.37
Moderate	18.45	18.05	8.50	2.82	2.22
High	0.74	1.51	1.21	0.67	0.44
Very high	0.00	0.03	0.03	0.17	0.10

The cross tabulation results between soil erosivity and slope of the area revealed (table 11) that high and very high erosive areas found in steep slopes, while most very low erosive areas were located in flat slope areas.

Table 12 Relationship between soil erosivity and major soils

Erosivity area (km <sup>2</sup> )	Major Soil type			
	Chromic Luvisol	Eutric Vertisol	Humic Nitosol	Rendzic Leptosol
Very low	120.00	213.66	6.38	27.82
Low	59.61	112.78	17.14	22.85
Moderate	2.18	31.05	9.01	7.83
High	0.00	2.25	0.50	1.81
Very high	0.00	0.00	0.00	0.34

As showed in table 12, very high and high erosive areas were detected in Rendzic leptosols which are highly sensitive to soil erosion. On the otherhand, very low and low soil erosive areas found in chromic luvisol and eutric vertisols.

Table 13 Relationship between soil erosivity and land cover class

Erosivity area (km <sup>2</sup> )	Land cover				
	Moderately Cultivated	Afro Alpine	Dominantly Cultivated	Urban	
Very low	240.91	87.14	39.79	0.03	
Low	22.38	59.61	130.22	0.17	
Moderate	2.86	2.18	44.56	0.47	
High	0.00	0.00	4.40	0.17	
Very high	0.00	0.00	0.34	0.00	

Dominantly cultivated areas were detected as very high erosive areas; while afro alpine and moderately cultivated areas found very low and low erosive areas (table 13).

### 4. Conclusions

Using RUSLE parameters by GIS and Remote sensing techniques guarantee the handling of spatially variable data and inaccessible area easily and efficiently. The findings of this study incorporates spatially distributed soil loss rate of Muga watershed. The annual soil loss of the watershed extends from 0.02 to 41.789 t/ha/year. Very high

soil loss was observed in the lower parts of the watershed at a rate exceeding the tolerable soil loss limit. This was due to the steepness of the slope and low management practices /absence of supporting the practice. This severe soil loss area could threaten agricultural productivity and extends its offsite effect of sedimentation on Abay River. In this study, slope length and gradient (LS) factor was the primary influential RUSLE parameter followed by Support Practice (P) Factor.

Substantial investment on soil and water conservation measure could be done in the lower part of the watershed irrespective of the watershed logic (conservation measures should be started at the upper part of the watershed). RUSLE does not consider gully erosion which is now seriously dissected and fragments grazing and farmlands. Thus, further study on gully erosion estimation and sedimentation is recommended.

### Acknowledgments

I am very grateful to thank Debre Tabor University, and Ministry of Water, Irrigation and Electricity (MoWIE) for providing me meteorological & hydrological data freely.

### Data Availability

The data used to support the findings of this study are included with the article.

### Conflict of Interest

The authors declare that there are no conflicts of interest regarding the publication of this paper.

### References

- Aster D., 200). Use of Geospatial Technologies for Environmental Protection in Ethiopia. Environmental Protection Authority. United Nations/European Space Agency/Sudan. Remote Sensing Workshop on the Use of Space Technology for Natural Resources Management Environmental Monitoring and Disaster Management. April 4-8, 2004 Sudan, Khartoum.
- BCEOM, 1998. Abbay River Basin Integrated Development Master Plan, Main Report. Ministry of Water Resources: Addis Ababa.
- D., Ahmed, M., Degu, Y., Kebebew, Z., Hodel, E., Amdihun, A., Mekuriaw, A., Debele, B., Deichert, G., Hurni, H., 2015. Soil Degradation and Sustainable Land Management in the Rainfed Agricultural Areas of Ethiopia: An Assessment of the Economic Implications. Economics of Land Degradation (ELD) Ethiopia Case Study Report for the Economics of Land Degradation Initiative. 94 pp. Retrieved 21 July 2016, from [www.eld-initiative.org](http://www.eld-initiative.org).
- Demeke GG., Andualem TG., 2018. Application of Remote Sensing for Evaluation of Land Use Change Responses on Hydrology of Muga Watershed, Abbay River Basin, Ethiopia. *J Earth Sci Clim Change* 9: 493. doi: 10.4172/2157-7617.1000493
- Descheemaeker, K., Nyssen, J., Rossi, J., Poesen, J., Haile, M., Moeyersons, J., Deckers, J., 2006. Sediment deposition and pedogenesis in exclosures in the Tigray Highlands, Ethiopia. *Geoderma* 132, 291–314.
- EHR, 1984. Annual Research Report (1983-1984), Ministry of Agriculture, Addis Ababa. Erosion in Ethiopia. Lund University Press.
- Engel, B., 2005. Estimating Soil Erosion Using RUSLE (Revised Universal Soil Loss Equation) Using Arc View. Unpublished.
- FAO, 1984. Ethiopian Highland Reclamation Study (EHR): Final Report. Vol. 1-2.
- FAO, 1989. Reconnaissance Physical Land Evaluation in Ethiopia. Addis Ababa, Ethiopia
- Haregeweyn, N., Atsushi Tsunekawa, Jean Poesen, Mitsuru Tsubo, Derege Tsegaye Meshesha, Ayele Almaw Fenta, Jan Nyssen, Enyew Adgo, (2017). Comprehensive assessment of soil erosion risk for better land use planning in river basins: a Case study of the Upper Blue Nile River. The science of the total environment. <http://dx.doi.org/10.1016/j.scitotenv.2016.09.019>
- Haregeweyn, N., Tsunekawa, A., Tsubo, M., Meshesha, D., Adgo, E., Poesen, E., Schuett, B., 2016. Analyzing the hydrologic effects of region-wide land and water development interventions: a case study of the Upper Blue Nile basin. *Reg. Environ. Chang.* 16, 951–966. <http://dx.doi.org/10.1007/s10113-015-0813-2>.
- Helden, U., 1987. An Assessment of Woody Biomass, Community Forests, Land Use, and Soil Erosion in Ethiopia. Lund University Press.
- Hurni H., 1985a. Soil Conservation Manual for Ethiopia. Ministry of Agriculture: Addis Ababa.
- Hurni H., 1985b. Erosion–productivity–conservation systems in Ethiopia. Paper Presented at the 4th International Conference on Soil Conservation, 3–9 November 1985, Maracay, Venezuela.
- Hurni, H., 1985. Erosion-productivity conservation systems in Ethiopia. Paper presented at IV ISCO conference, Venezuela.
- Hurni, H., 1993. Land Degradation, famine and resource scenarios in Ethiopia. In *World Soil Erosion and Conservation*, ed. D. Pimentel. Cambridge University press, Cambridge.

- Kunta, K., 2009. Effects of Geographic Information Quality on Soil Erosion Prediction.
- Lulseged, T. and Vlek, P.L.G., 2005. GIS-based landscape characterization to assess soil erosion and its delivery potential in the highlands of northern Ethiopia. In Proceedings of the 1st International Conference on Remote Sensing and Geoinformation Processing in the assessment and monitoring of land degradation and desertification. 7 – 9 September, Trier, Germany. 332-339.
- Mitasova H. and Mitas Z., 1999. Modeling soil detachment with RUSLE 3d using GIS. The University of Illinois at Urbana –Champaign.
- Moore, I.D. and Burch G.J., 1986b. Modeling erosion and deposition: topographic effects. *Transactions of the ASAE*. Vol.26: 1624-1630.
- Moore, I.D., and Burch, G.J., 1986a. Physical basis of the length-slope factor in the Universal Soil Loss Equation. *Soil Science Society of America Journal*, 50(5): 1294-1298.
- Morgan, R.P.C., 2005. Soil Erosion and Conservation. 3rd Edn., Blackwell Publishing, Oxford, ISBN:1405117818, 9781405117814, pp: 304.
- NMSA, 2001. Initial National Communication of Ethiopia to the United Nations Framework Convention on Climate Change (UNFCCC) National Meteorological Service Agency, Addis Ababa, Ethiopia.
- Reusing, M., T. Schneider, and U. Ammer, 2000. Modeling Soil Loss rates In the Ethiopian Highlands by Integration of High-Resolution MOMS-02/D2-Stereo-data in a GIS. *Int. Journal of Remote sensing*, pp: 1885-1896
- Simms, A.D., Woodroffe, and Jones, 2003. Application of RUSLE for erosion management in a coastal catchment, Southern NSW. Proceedings of the International Congress on Modeling and Simulation: Integrative Modeling of Biophysical, Social and Economic Systems for Resource Management Solutions, July 14-17, 2003, Townsville, Australia, pp: 678-683.
- Sonneveld, B.G.J.S., Keyze, M.A., Stroosnijder, L., 2011. Evaluating quantitative and qualitative models: an application for nationwide water erosion assessment in Ethiopia. *Environ. Model Softw.* 26, 1161–1170.
- Sutcliffe, J.P., 1993. Economic assessment of land degradation in the Ethiopian highlands: A case study. National conservation strategy secretariat, Ministry of planning and economic development, Addis Ababa, Ethiopia.
- Tamene, L. and Vlek, P. L. G., 2007. Assessing the potential of changing land use for reducing soil erosion and sediment yield of catchments: a case study in the highlands of northern Ethiopia.
- Taye, G., Poesen, J., Van Wesemael, B., Goosse, T., Teka, D., Deckers, J., Hallet, V., Haregeweyn, N., Nyssen, J., Maetens, W., 2013. Effects of land use, slope gradient, and soil and water conservation techniques, on runoff and soil loss in a semi-arid environment. *Journal of Physical Geography* 34 (3), 236–259.
- Wischmeier, W.H. and Smith, D., 1978. Predicting rainfall erosion losses: a guide to conservation planning. *USDA-ARS Agriculture Handbook N° 537*. : p.58
- Xu, Y. Shao, X.X., Kong, J., Peng, and Cai. Y., 2008. Adapting the RUSLE and GIS to model soil erosion risk in a mountains karst watershed, Guizhou Province, China, *Environmental Monitoring and Assessment*, vol. 141, pp. 275–286.
- Zemenu and Amare, 2014. Adoption of soil conservation practices in North Achefer District, Northwest Ethiopia.